

# RETREAD SPECIFICATIONS

The specs listed below are a recommendation only. Buffing equipment can vary and, as such, the specs below should be verified for each different style of buffer. Buff profile should be verified using pilot skives of 3/32" across buffed tread surface.

Size	Pattern	Buffed Crown Radius		Buffed Crown Width		Rim Width
		mm	in	mm	in	in
11R22.5	ST355	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
265/70R19.5	RH621	610.0	24.0	200.0	7.87	7.50
285/70R19.5		610.0	24.0	230.0	9.06	8.25
295/80R22.5		660.0	26.0	220.0	8.66	9.00
315/80R22.5		762.0	30.0	240.0	9.45	9.00
11R22.5	TR528	660.0	26.0	210.0	8.27	8.25
11R24.5		660.0	26.0	210.0	8.27	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	210.0	8.27	8.25
11R22.5	TR529	1321.0	52.0	225.0	8.86	8.25
11R24.5		1321.0	52.0	225.0	8.86	8.25
295/75R22.5		813.0	32.0	225.0	8.86	9.00
285/75R24.5		813.0	32.0	225.0	8.86	8.25
10R22.5	RH520	610.0	24.0	200.0	7.87	7.50
215/75R17.5	RH620	559.0	22.0	160.0	6.30	6.00
235/75R17.5		660.0	26.0	180.0	7.09	6.75
225/70R19.5		711.0	28.0	180.0	7.09	6.75
245/70R19.5		711.0	28.0	200.0	7.87	7.50
255/70R22.5		711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	8.25
245/70R17.5	RH647	711.0	28.0	200.0	7.87	6.75
255/70R22.5		711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	8.25
11R22.5		660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5	711.0	28.0	220.0	8.66	8.25	
215/75R17.5	RH647SP	559.0	22.0	175.0	6.89	6.00
225/70R19.5		711.0	28.0	185.0	7.28	6.75
245/70R19.5		711.0	28.0	225.0	8.86	7.50
215/75R17.5	RT785	508.0	20.0	155.0	6.10	6.00
10R22.5	RD796	610.0	24.0	200.0	7.87	7.50
11R22.5		660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
255/70R22.5		711.0	28.0	200.0	7.87	7.50
295/75R22.5		711.0	28.0	220.0	8.66	9.00
295/75R22.5		711.0	28.0	220.0	8.66	9.00

Size	Pattern	Buffed Crown Radius		Buffed Crown Width		Rim Width	
		mm	in	mm	in	in	
11R22.5	DT890	660.0	26.0	220.0	8.66	8.25	
11R24.5		610.0	24.0	220.0	8.66	8.25	
11R22.5	CD871	660.0	26.0	220.0	8.66	8.25	
11R24.5		660.0	26.0	220.0	8.66	8.25	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
285/75R24.5	711.0	28.0	220.0	8.66	8.25		
11R22.5	CD883	660.0	26.0	220.0	8.66	8.25	
11R24.5		660.0	26.0	220.0	8.66	8.25	
295/75R22.5		711.0	28.0	220.0	8.66	9.00	
285/75R24.5	711.0	28.0	220.0	8.66	8.25		
11R22.5	CD884	1016.0	40.0	225.0	8.86	8.25	
11R24.5		1016.0	40.0	225.0	8.86	8.25	
295/75R22.5		660.0	26.0	225.0	8.86	9.00	
285/75R24.5	813.0	32.0	225.0	8.86	8.25		
11R22.5	AP868	660.0	26.0	220.0	8.66	8.25	
11R24.5		610.0	24.0	220.0	8.66	8.25	
255/70R22.5		711.0	28.0	200.0	7.87	7.50	
275/70R22.5		762.0	30.0	230.0	9.06	8.25	
315/80R22.5	762.0	30.0	230.0	9.06	9.00		
11R22.5	RD798	711.0	28.0	235.0	9.25	8.25	
11R24.5		711.0	28.0	235.0	9.25	8.25	
11R22.5	DT990	660.0	26.0	220.0	8.66	8.25	
11R24.5		660.0	26.0	220.0	8.66	8.25	
12R22.5		660.0	26.0	240.0	9.45	9.00	
315/80R22.5	MS663	838.0	33.0	265.0	10.43	9.00	
385/65R22.5	DX770	1067.0	42.0	310.0	12.20	11.75	
425/65R22.5		1067.0	42.0	330.0	12.99	12.25	
445/65R22.5	DX775	1067.0	42.0	350.0	13.78	13.00	
385/65R22.5	DX670	1067.0	42.0	315.0	12.40	11.75	
385/55R22.5		991.0	39.0	335.0	13.19	12.25	
225/70R19.5	CD883SP	813.0	32.0	190.0	7.48	6.75	
245/70R19.5		711.0	28.0	200.0	7.87	7.50	
11R22.5	AP866	660.0	26.0	220.0	8.66	8.25	
11R24.5		610.0	24.0	220.0	8.66	8.25	
315/80R22.5		762.0	30.0	230.0	9.06	9.00	
11R22.5		RH652	660.0	26.0	220.0	8.66	8.25
11R24.5			660.0	26.0	220.0	8.66	8.25
255/70R22.5			711.0	28.0	210.0	8.27	7.50
295/75R22.5	711.0		28.0	220.0	8.66	9.00	
445/50R22.5	TR601	1245.0	49.0	400.0	15.75	14.00	
445/50R22.5	CD901	1245.0	49.0	400.0	15.75	14.00	